

LoRa Alliance Member

eBeat Arm Band

LoRaWAN® Device for Continuous Health Monitoring

The eBeat Arm Band by TEKTELIC is the ideal solution to continuously monitor the health and well-being of medical facility patients, senior care residents, or any other individual for potential respiratory illness or other health indicators requiring intervention. This specialized device is designed to continuously monitor an individuals body temperature, one of the most common symptoms of respiratory illness. An adjustable, washable arm-band strap ensures the device can be worn comfortably and discreetly in any situation.

- Hospitals & Medical Facilities Remote Vital Monitoring
- Senior Care Facilities
- **Home Care Monitoring**
- **High Density Workplaces**
- **Schools & Universities**



Key Features & Functions

- **Body Temperature Monitoring**
- SP02 Monitoring
- Heart Rate Monitoring
- Respiration Rate Monitoring
- Adjustable, Washable Arm-Band Strap
- **>> Fully Integrated Application**
- **)** Sleek, Unobtrusive Design Up to
- 4 Month Battery Life



Technical and Functional Specifications General System Parameters

| Operational Temperature | 0°C to 50°C |
|--------------------------------------|--------------------------------------|
| Intended Operational Temperature* | 32°C to 42°C |
| Body Temperature Accuracy | 0.05°C from 35° to 40°C |
| SP02 Monitoring | ±2 %with range of 70 to 100% |
| Heart Rate Monitoring | ±5 bpm with range from 30 to 240 bpm |
| Ingress Protection | IP30 |
| Device Size | 66.0 x 36.2 x 11.7 mm |
| Strap Size | Adjustable |
| Battery | CR2477 |
| Estimated Battery Life | 4 months |

^{*}Device will enter a Low-Power Sleep Mode outside this range







eBeat Arm Band



LoRaWAN® Device for Continuous Health Monitoring

Technical and Functional Specifications

LoRa Parameters

| RF Power | 8 dBm |
|-------------------|------------------|
| RF Sensitivity | up to -137 dBm |
| ISM Band | All Global Bands |
| Antenna | Internal |
| LoRa Device Class | Class A |

Regulatory Compliance

| Safety | IEC 60950-1 (CE) |
|------------|-----------------------|
| Regulatory | ETSI EN 300 220 |
| | ETSI EN 301-489-1/-3 |
| | FCC 15.247 FCC 15.209 |



